

# OPEN COUNTRY A/T II



OPEN COUNTRY A/T II is a progressive all-terrain tire. Balancing off-road performance and on-road comfort, the OPEN COUNTRY A/T II is renowned for achieving exceptional mileage. Functional tread pattern and side biters for performance with looks to match. For passenger it provides comfort, whereas for light-truck it provides puncture resistance. Interlocking tread blocks with tie bars create stability, extending tread life.

INCH	ASPECT RATIO	TIRE SIZE	LOAD INDEX	SPEED SYMBOL	RF/XL	SIDE
15	-	30X950 R15	104	S	-	OWL
		31X1050 R15	109	S	-	OWL
	70	215/70 R15	98	H	-	-
		P225/70 R15	100	T	-	OWL
		P235/70 R15	102	S	-	-
		255/70 R15	112/110	S	-	-
		LT265/70 R15	109/105	S	-	-
		265/70 R15	112	S	-	-
	75	P205/75 R15	97	S	-	-
		P215/75 R15	100	S	-	OWL
		P225/75 R15	102	S	-	OWL
		LT235/75 R15	110/107	R	-	OWL
		LT235/75 R15	104/101	S	-	OWL
		P235/75 R15	108	S	XL	OWL
16	65	P265/75 R15	112	S	-	OWL
		255/65 R16	109	H	-	-
	70	P215/70 R16	99	S	-	-
		P225/70 R16	101	T	-	OWL
		P235/70 R16	104	T	-	-
		LT245/70 R16	118/115	R	-	OWL
P245/70 R16		106	S	-	-	
P245/70 R16		106	S	-	OWL	
16	70	P255/70 R16	109	S	-	OWL
		LT265/70 R16	121/118	R	-	OWL
		P265/70 R16	111	T	-	OWL
		LT275/70 R16	119/116	S	-	OWL

## PERFORMANCE CHARACTERISTICS

	1	2	3	4	5
DRY PERFORMANCE	■	■	■	■	■
RIDE COMFORT	■	■	■	■	■
TREAD LIFE	■	■	■	■	■
OFFROAD TRACTION	■	■	■	■	■



- Function tread pattern and side bites for performance with looks to match.
- Passenger structure for comfort. Light-truck structure for puncture resistance.
- Interlocking tread blocks with tie bars create stability, extending tread life.
- Self cleaning, with staggered shoulders and deep centre grooves including stone ejectors.

INCH	ASPECT RATIO	TIRE SIZE	LOAD INDEX	SPEED SYMBOL	RF/XL	SIDE
16	75	LT225/75 R16	115/112	Q	-	-
		P225/75 R16	104	S	-	-
		LT245/75 R16	108/104	S	-	OWL
		LT245/75 R16	120/116	S	-	OWL
		P245/75 R16	109	S	-	-
		P245/75 R16	109	S	-	OWL
		LT265/75 R16	112/109	T	-	OWL
		P265/75 R16	114	T	-	-
	P265/75 R16	114	T	-	OWL	
	LT285/75 R16	126/123	R	-	OWL	
16	85	LT215/85 R16	115/112	Q	-	-
		LT235/85 R16	120/116	R	-	-
17	-	35X1250 R17	121	R	-	-
		235/60 R17	10	H	-	-
	60	P275/60 R17	110	T	-	-
		225/65 R17	102	H	-	-
		245/65 R17	111	S	XL	OWL
		LT255/65 R17	119/116	S	-	-
		LT265/65 R17	120/117	R	-	OWL
		LT275/65 R17	121/118	R	-	-
	65	LT285/65 R17	121/118	S	-	-
		LT225/70 R17	115/112	S	-	-
70		LT245/70 R17	114	S	-	-
		LT265/70 R17	121/118	S	-	OWL
70	P265/70 R17	113	S	-	OWL	
	P265/70 R17	113	S	-	-	
	LT285/70 R17	121/118	S	-	OWL	
	75	LT245/75 R17	121/118	S	-	-
18	60	285/60 R18	120	S	XL	-
		P265/65 R18	112	S	-	-
	65	LT275/65 R18	123/120	S	-	OWL
		LT275/65 R18	113/110	T	-	OWL
		LT285/65 R18	125/122	S	-	-
		70	LT275/70 R18	125/122	S	-
20	50	265/50 R20	111	T	XL	-
		285/50 R20	116	T	XL	-
	55	P275/55 R20	111	S	-	-
		LT305/55 R20	121	S	-	-
60	P275/60 R20	114	T	-	-	
22	-	37X1250 R22	127	Q	-	-

OWL = Outlined White letter